


ANDALUCIA 20-40 Guide laterali . Side Rails




Tenda con profili guida da installare in orizzontale, dotata di traverse scorrevoli per lo svolgimento e per l'impacchettamento del telo (onde ogni 50 cm circa). Movimentazione di tipo manuale con asta. Vengono utilizzate traverse in tubo diametro 18 mm. per larghezze max di mt. 1.80 e per larghezze superiori fino a mt. 3.60, un profilo ovale di dimensioni 43x26 mm. Struttura in alluminio verniciata con polveri poliestere eseguita seguendo rigidi standard qualitativi. Viteria esposta in acciaio inox. Tenda indicata per applicazioni sotto pergole, verande, lucernai.


Awning with profiles to be installed in an horizontal position, endowed with flowing crossbars for the unrolling and the wrapping up of the cloth (waves each 50 cm). Manual working by pole. For max. width of mt. 1.80 crossbars in pipe diam. 18 mm. are used for longer widths up to mt. 3.60 it is used an oval profile whose dimension is mm. 43x26. Aluminium structure painted by polyester following rigid qualitative standards. Exposed bolts and screws made of stainless steel. Ideal awning for installation below wood pergolas, verandas and skylights.



Andalucia 40



Andalucia 20



Guide Laterali . Side rail

Standard



9010



8017

Optional

